

# ISUZU D-MAX MY21

## 3600KG GVM UPGRADE



**Kit #: ISUZKIT008-GVM**

Capacities	Lovells	OE
GVM	3600kg	3100kg
GCM	6200kg	5950kg
Front Axle	1450kg	
Rear Axle	2150kg	
Towing	3500kg	3500kg

### DATES

All body types  
07/2020 on

### SPRING OPTIONS

FRONT: IFS-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg  
IFR-002 – Load bearing front accessories, including Bullbar. Axle capacities over 1300kg

REAR: IS-003EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

### SHOCK PART NUMBERS

FRONT: 64611038 (Twin Tube Shocks)  
REAR: 6462258B (Twin Tube Shocks)

### OTHER KIT COMPONENTS

Eye & Shackle Bushed  
U-Bolts  
Greaseable Shackles  
Greaseable Pins  
Cat 6 Indicators  
Tyre Placard  
Decals

### NOTES:

#### SVI Plate Location:

Drivers Side A Pillar

#### Lovells Approval Number:

VTA 051523

#### Tyres:

**TYRES MUST BE CHANGED TO  
A MINIMUM LOAD RATING  
OF 111 & SPEED RATING OF Q**

#### Special Requirements:

**CAT6 indicators are required  
to be compliant**

### TYRE – LOADING INFORMATION

GVM- 3600kg	FRONT AXLE	REAR AXLE
TYRE SIZE (minimum) (Tyre Load Index minimum)	LT255/65 R17 (111) LT265/60 R18 (111)	LT255/65 R17 (111) LT265/60 R18 (111)
RIM SIZE (minimum)	17 x 7J 18 x 7.5J	17 x 7J 18 x 7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE	200kPa (200kPa)	250kPa (200kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1450kg	2150kg
( ): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE		
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.		
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q".		
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION		
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG		
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE		
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg		
LS-Isuzu D Max / Mazda BT50C / Isuzu DMax RG_NB_02		

# ISUZU D-MAX MY21

## 3600KG GVM UPGRADE

With Cooling Upgrade for Extra GCM

Kit #: ISUZKIT008-GVM-R



Capacities	Lovells	OE
GVM	3600kg	3100kg
GCM	6900kg	5950kg
Front Axle	1450kg	
Rear Axle	2150kg	
Towing	3500kg	3500kg

### DATES

All body types  
07/2020 on

### SPRING OPTIONS

FRONT: IFS-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg  
IFR-002 – Load bearing front accessories, including Bullbar. Axle capacities over 1300kg  
REAR: IS-003EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

### SHOCK PART NUMBERS

FRONT: 64611038 (Twin Tube Shocks)  
REAR: 6462258B (Twin Tube Shocks)

### OTHER KIT COMPONENTS

Eye & Shackle Bushed  
U-Bolts  
Greaseable Shackles  
Greaseable Pins  
Lovells Radiator  
Cat 6 Indicators  
Tyre Placard  
Decals

### NOTES:

#### SVI Plate Location:

Drivers Side A Pillar

#### Lovells Approval Number:

VTA 051523

#### Tyres:

**TYRES MUST BE CHANGED TO  
A MINIMUM LOAD RATING  
OF 111 & SPEED RATING OF Q**

#### Special Requirements:

**CAT6 indicators are required  
to be compliant**

### TYRE – LOADING INFORMATION

GVM- 3600kg	FRONT AXLE	REAR AXLE
TYRE SIZE (minimum) (Tyre Load Index minimum)	LT255/65 R17 (111) LT265/60 R18 (111)	LT255/65 R17 (111) LT265/60 R18 (111)
RIM SIZE (minimum)	17 x 7J 18 x 7.5J	17 x 7J 18 x 7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE	200kPa (200kPa)	250kPa (200kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1450kg	2150kg
( ): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE		
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.		
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q".		
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg		

LS-Isuzu D Max / Mazda BT50C / Isuzu DMax RG\_NB\_02