

TOYOTA HILUX GUN SERIES 3500KG GVM UPGRADE



Kit #: TOYKIT077-GVM

Capacities	Lovells	OE
GVM	3500kg	3000kg
GCM	6550kg	5850kg
Front Axle	1480kg	
Rear Axle	2050kg	
Towing	3500kg	3500kg

<u>DATES</u>
All body types 10/2015 on

<u>SPRING OPTIONS</u>	
FRONT:	TFR-118 – Minimal load bearing front accessories, including Bullbar. 0 – 100kg Constant Load TFR-118HD – Minimal load bearing front accessories, including Bullbar. 100 – 150kg Constant Load
REAR:	TL-62EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

<u>SHOCK PART NUMBERS</u>	
FRONT:	64610087A (Twin Tube Shocks)
REAR:	64612525 (Twin Tube Shocks)

<u>OTHER KIT COMPONENTS</u>
Eye & Shackle Bushed
U-Bolts
Greasable Shackles
Greasable Pins
Tyre Placard
Decals

<u>NOTES:</u>
SVI Plate Location: Below Front LHS Door sticker for Single & Dual Cabs, Base LHS C Pillar for Extra Cab
Lovells Approval Number: VTA 047909
Tyres: TYRES MUST HAVE A MINIMUM LOAD RATING OF 109, SINGLE CAB MAY NOT COMPLY
Special Requirements: SR5 model will require Headlight Adjusting Rod

<u>TYRE – LOADING INFORMATION</u>						
	FRONT AXLE			REAR AXLE		
TYRE SIZE (minimum) <i>(Tyre Load Index minimum)</i>	225/70R17C <i>(109)</i>	265/65 R17 <i>(109)</i>	265/60 R18 <i>(109)</i>	225/70R17C <i>(109)</i>	265/65 R17 <i>(109)</i>	265/60 R18 <i>(109)</i>
RIM SIZE (minimum)	17X6J	17X7.5J	18X7.5J	17X6J	17X7.5J	18X7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (200kPa)	250kPa (200kPa)	250kPa (200kPa)	250kPa (200kPa)	250kPa (200kPa)	250kPa (200kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1480kg			2050kg		
() TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q" (160km/h). SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE. THE GVM OF THIS VEHICLE MUST NOT EXCEED 3500kg.						
LS Hilux8Gen Ver 3						