

ISUZU D-MAX MY12

3600KG GVM UPGRADE



Kit #: ISUZKIT006-GVM

Capacities	Lovells	OE
GVM	3600kg	2950kg
GCM	6200kg	5950kg
Front Axle	1450kg	
Rear Axle	2150kg	
Towing	3500kg	3500kg

<u>DATES</u>
All body types 07/2020 on

<u>SPRING OPTIONS</u>	
FRONT:	IFS-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg IFR-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1300kg
REAR:	IS-003EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

<u>SHOCK PART NUMBERS</u>	
FRONT:	64611038 (Twin Tube Shocks)
REAR:	6462258B (Twin Tube Shocks)

<u>OTHER KIT COMPONENTS</u>
Eye & Shackle Bushed
U-Bolts
Greasable Shackles
Greasable Pins
Cat 6 Indicators
Tyre Placard
Decals

<u>NOTES:</u>
SVI Plate Location: State Compliance Only
Lovells Approval Number: VTA 048580
Tyres: TYRES MUST BE CHANGED TO A MINIMUM LOAD RATING OF 111 & SPEED RATING OF Q
Special Requirements: CAT6 indicators are required to be compliant

<u>TYRE – LOADING INFORMATION</u>		
GVM- 3600kg	FRONT AXLE	REAR AXLE
TYRE SIZE (minimum) (Tyre Load Index minimum)	245/70 R16 (111)	245/70 R16 (111)
RIM SIZE (minimum)	6J, 6.5J, 7J, 7.5J	6J, 6.5J, 7J, 7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (200kPa)	250kPa (200kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1450kg	2150kg
(:) TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE		
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.		
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q".		
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION		
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE		
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg		

LS-Isuzu D Max- LS1D TP03 Version 3