TOYOTA 300 SERIES 3600KG GVM UPGRADE

Kit #: TOYKIT086-GVM-LC36-NB1

Capacities	Lovells	OE
GVM	3600kg	3300kg
GCM	7100kg *	6800kg
Front Axle	1630kg	1630kg
Rear Axle	1970kg	1930kg
Towing	3500kg	3500kg

DATES

08/2021 on

SPRING OPTIONS

FRONT: TFS-140 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1500kg
TFR-140 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1500kg

REAR: TRR-141 – Minimal load bearing rear accessories.

SHOCK PART NUMBERS

FRONT: 64612855 (Twin Tube Shocks)

REAR: 64612856 (Twin Tube Shocks)

OTHER KIT COMPONENTS

Reverse light & Harness
Reverse Light Bracket
Decals
Tyre Placard
CAT6 Indicators

NOTES:

SVI Plate Location:
Passengers Side B Pillar

Lovells Approval Number:
VTA 064836

Tyres:
Factory tyres meet minimum specification

Special Requirements:
Reverse Light to be fitted and OE lights covered or disconnected.

CAT6 Indicators must be fitted

Always consult Lovells master data capacities spreadsheet, these data sheets are a guide only

TYRE – LOADING INFORMATION

TYRE SIZE	RIM SIZE	RECOMMENDED COLD INFLATION PRESSURE (kPa)		INFLATION PRESSURE AT MAX LOAD (kPa)	
		FRONT AXLE	REAR AXLE	FRONT AXLE	REAR AXLE
245/75R17 (112H)	17x7J	230	230	230	240
LT245/75R17 (116R)	17x7J	250	250	250	350
265/65R18 (112R)	18x7.5J	230	230	230	240
LT265/65R18 (116R)	18x7.5J	250	250	250	350
LT275/65R18 (116R)	18x7.5J	250	250	250	300
275/55R20 (116R)	20x8J	230	230	230	240
265/55R20 (112R)	20x8J	230	230	230	240
LOAD CARRYING CAPACITY PER AXLE (maximum)		FRONT AXLE 1630kg		REAR AXLE 1970kg	

SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 250KG

THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg

LS35-TOYOTA LC300_NB1_V4

*GCM revision may not be available in all states.

Ph: +61 2 9820 6800
Email: sales@lovells.com.au
www.lovellsauto.com.au

LOVELLS AUTOMOTIVE SYSTEMS

24th Sept 2025