

MAZDA BT-50 MY21

3600KG GVM UPGRADE



Kit #: ISUZKIT008-GVM

Capacities	Lovells	OE
GVM	3600kg	3100kg
GCM	6200kg	5950kg
Front Axle	1450kg	
Rear Axle	2150kg	
Towing	3500kg	3500kg

DATES

All body types
07/2020 on
3.0 Ltr Engine only

SPRING OPTIONS

FRONT: IFS-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg
IFR-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1300kg
REAR: IS-003EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

SHOCK PART NUMBERS

FRONT: 64611038 (Twin Tube Shocks)
REAR: 6462258B (Twin Tube Shocks)

OTHER KIT COMPONENTS

Eye & Shackle Bushed
U-Bolts
Greaseable Shackles
Greaseable Pins
Cat 6 Indicators
Tyre Placard
Decals

NOTES:

SVI Plate Location:

Drivers Side A Pillar

Lovells Approval Number:

VTA 051540 / 060210

Tyres:

TYRES MUST BE CHANGED TO A MINIMUM LOAD RATING OF 111 & SPEED RATING OF Q

Special Requirements:

CAT6 indicators are required to be compliant

TYRE – LOADING INFORMATION

GVM- 3600kg	FRONT AXLE	REAR AXLE
TYRE SIZE (minimum) (Tyre Load Index minimum)	LT255/65 R17 (111) LT265/60 R18 (111)	LT255/65 R17 (111) LT265/60 R18 (111)
RIM SIZE (minimum)	17 x 7J 18 x 7.5J	17 x 7J 18 x 7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE	200kPa (200kPa)	250kPa (200kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1450kg	2150kg
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE		
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.		
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q".		
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION		
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG		
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE		
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg		
LS-Isuzu D Max / Mazda BT50C / Isuzu DMax RG_NB_02		

MAZDA BT-50 MY21

3600KG GVM UPGRADE

With Cooling Upgrade for Extra GCM

Kit #: ISUZKIT008-GVM-R



Capacities	Lovells	OE
GVM	3600kg	3100kg
GCM	6900kg	5950kg
Front Axle	1450kg	
Rear Axle	2150kg	
Towing	3500kg	3500kg

DATES

All body types
07/2020 on
3.0 Ltr Engine only

SPRING OPTIONS

FRONT: IFS-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg
IFR-002 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1300kg
REAR: IS-003EHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

SHOCK PART NUMBERS

FRONT: 64611038 (Twin Tube Shocks)
REAR: 6462258B (Twin Tube Shocks)

OTHER KIT COMPONENTS

Eye & Shackle Bushed
U-Bolts
Greaseable Shackles
Greaseable Pins
Lovells Radiator
Cat 6 Indicators
Tyre Placard
Decals

NOTES:

SVI Plate Location:

Drivers Side A Pillar

Lovells Approval Number:

VTA 051540 / 060210

Tyres:

**TYRES MUST BE CHANGED TO
A MINIMUM LOAD RATING
OF 111 & SPEED RATING OF Q**

Special Requirements:

**CAT6 indicators are required
to be compliant**

TYRE – LOADING INFORMATION

GVM- 3600kg	FRONT AXLE	REAR AXLE
TYRE SIZE (minimum) (Tyre Load Index minimum)	LT255/65 R17 (111) LT265/60 R18 (111)	LT255/65 R17 (111) LT265/60 R18 (111)
RIM SIZE (minimum)	17 x 7J 18 x 7.5J	17 x 7J 18 x 7.5J
RECOMMENDED COLD TYRE INFLATION PRESSURE	200kPa (200kPa)	250kPa (200kPa)
- At maximum GVM		
- (No Load)		
LOAD CARRYING CAPACITY PER AXLE (maximum)	1450kg	2150kg
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE		
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.		
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q".		
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION		
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG		
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE		
THE GVM OF THIS VEHICLE MUST NOT EXCEED 3600kg		

LS-Isuzu D Max / Mazda BT50C / Isuzu DMax RG_NB_02

Ph: +61 2 9820 6800

Email: sales@lovelles.com.au
www.lovellesaoto.com.au

